



### Features

- 7" 800 x 480 TFT LCD, LED Backlight
- Fan-less Cooling System
- Two Gigabit Ethernet Ports
- COM2 and COM3 RS-485 support MPI 187.5K, please use one at one time
- PCB coating process ensures high reliability to resist from corrosion in harsh environment
- Built-in Power Isolation
- NEMA4 / IP65 Compliant Front Panel
- Built-in EasyAccess 2.0 License

<b>Display</b>	Display	7" TFT
	Resolution	800 x 480
	Brightness (cd/m <sup>2</sup> )	400
	Contrast Ratio	500:1
	Backlight Type	LED
	Backlight Life Time	>30,000 hrs.
	Colors	16.7M
	LCD Viewing Angle (T/B/L/R)	70/50/70/70
<b>Touch Panel</b>	Type	4-wire Resistive Type
	Accuracy	Active Area Length(X)±2%, Width(Y)±2%
<b>Memory</b>	Flash	128 MB
	RAM	128 MB
<b>Processor</b>		32 bits RISC Cortex-A8 600MHz
<b>I/O Port</b>	SD Card Slot	N/A
	USB Host	USB 2.0 x 1
	USB Client	N/A
	Ethernet	10/100/1000 Base-T x 2
	COM Port	COM1: RS-232, COM2: RS-485 2W/4W, COM3: RS-232/RS-485 2W*
	RS-485 Dual Isolation	N/A
	CAN Bus	N/A
	HDMI	N/A
	Audio Output	N/A
	Video Input	N/A
<b>RTC</b>		Built-in
<b>Power</b>	Input Power	24±20%VDC
	Power Isolation	Built-in
	Power Consumption	600mA@24VDC*
	Voltage Resistance	500VAC (1 min.)
	Isolation Resistance	Exceed 50MΩ at 500VDC
	Vibration Endurance	10 to 25Hz (X, Y, Z direction 2G 30 minutes)
<b>Specification</b>	PCB Coating	Yes
	Enclosure	Plastic

	Dimensions WxHxD	7.89 x 5.76 x 1.34 inch
	Panel Cutout	7.56 x 5.43 inch
	Weight	Approx. 1.32 lbs
	Mount	Panel mount
<b>Environment</b>	Protection Structure	UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel
	Storage Temperature	-20° ~ 60°C (-4° ~ 140°F)
	Operating Temperature	0° ~ 50°C (32° ~ 122°F)
	Relative Humidity	10% ~ 90% (non-condensing)
<b>Certificate</b>	CE	CE marked
	ATEX	ATEX Zone 2/22 Category 3 G/D
	UL	cULus Listed
<b>Software</b>	EasyBuilder Pro V5.02.01 or later versions	

\*Only Tx & Rx (no RTS/CTS) may be used for COM1 RS-232 when COM3 RS-232 is also used.

\*Includes power consumption of USB device.

## Dimensions

**Top View**  
200.3mm [7.89"]

**Front View**  
146.3mm [5.76"]

**Side View**  
7.4mm [0.29"]  
22.5mm [0.89"]  
5.1mm [0.20"]

**Cutout Dimensions**  
192mm [7.56"]  
138mm [5.43"]  
192mm [7.559"] W x 138mm [5.433"] H

**Rear View**  
189.6mm [7.46"]  
135.6mm [5.34"]

**Bottom View**  
34mm [1.36"]

<b>a.</b>	DIP SW
<b>b.</b>	Fuse
<b>c.</b>	Power Connector
<b>d.</b>	COM2 RS-485 2W/4W, COM3 RS-485 2W
<b>e.</b>	USB Host Port
<b>f.</b>	COM1 RS-232, COM3 RS-232
<b>g.</b>	LAN 2
<b>h.</b>	LAN 1

### Ordering Information

**MT8073iE1:**  
7" 800 x 480 TFT LCD HMI, Built-in 128 MB flash memory / 128 MB DDR2 RAM on board, Built-in EasyAccess 2.0 license

**Pin Assignment:**
**COM1/COM3 [RS232] 9 Pin, Male, D-sub**

PIN#	Symbol	COM1 [RS232]	COM3 [RS232]
1	Not used		
2	RxD	Received Data	
3	TxD	Transmitted Data	
4	Not used		
5	GND	Ground	
6	Not used		
7	RTS	Ready to send	Transmitted Data
8	CTS	Clear to send input	Received Data
9	GND	Ground	

**COM2 / COM3 [RS485] 9 Pin, Female, D-sub**

PIN#	Symbol	COM2 [RS485]2w	COM2 [RS485]4w	COM3 [RS485]
1	Rx-	Data-	Rx-	
2	Rx+	Data+	Rx+	
3	Tx-		Tx-	
4	Tx+		Tx+	
5	GND	Ground		
6	Data-			Data-
7	Not used			
8	Not used			
9	Data+			Data+

Contact: WEINTEK HMI Corp. TEL: +1(510) 897-6670 Web: [weintekhmi.com](http://weintekhmi.com)

MT8073iE1\_DataSheet\_ENG\_20160314